

DLC1500ARTM-01

15 inch Rear-Mount Touch Monitor

RTM-T Series P-CAP Multi-Touch Screen and none-Edge-LED LCD Monitor



✧ Overview

RTM series touch display is a touch display supporting capacitance multi touch and LED backlight, providing excellent picture quality with wide viewing angle and high resolution. Integrated PCT capacitance multi touch, it can achieve a flat surface appearance similar to iPad and excellent multi touch experience. In principle, it can realize touch performance that is not afraid of light, dust and water. It has a fashionable black aluminum oxide. It is the best partner in retail, catering, gaming, video game and medical industry. With flexible desktop base, the product can be safely fixed in the required place at any angle.



✧ Features

Easy to Use

Support a variety of input video signals, standard Touch signal input, plug & play and power & signal on out.

High Quality LED Panel

Full range CPA E-LED backlight monitors, HD resolution (1024 x 768).

Reliable and Professional Design

Designed with elegant full metal structure & aluminum bezel for outstanding image clarity.

Esay Installation

Supports optional standard VESA wall mount brackets and embedded install.

Flat Surface Design

Similar to iPad flat surface delivers durable dust & water resistance, improving product reliability and Lifetime.

Projected Capacitive Multi-touch

10 points accurate touch response.

Multi touch support

Support windows multi touch protocol, multi screen calibration function.

Supported OS

Windows 7/10, Android, Linux, Mac OSX

✧ Specifications

Display	
LED Panel	CPA-Panel, 15 inch
Backlight	E-LED (edge-lit)
Viewable Area	304.1 x 228.1mm
Brightness	300 cd/m2
Contrast Ratio	1500:1
Viewing Angle	85° /85° H/V
Response Time	35ms (GTG)
Number of Colors	16.2M Colors
Native Resolution	1024x768 (4:3), HD
Video Frequency	60Hz
Video Interface	VGA x1 / HDMI x1
Input Resolution	1024 x 768 @ 60Hz

Touch	
Touch Points	10 (HID, only with supported OS)
Touch Technology	Projective Capacitive (PCAP)
Touch Method	Finger, glove (latex) Active & passive stylus pen
Glass Overlay	4mm tempered glass Optional AG / AR surface finish
Water Resistance	Support touch in water fog and light rain Little drops of water will not cause drift



Response Time	16ms
Report Rate	>100Hz
Touch Interface	USB (Type B) x1
Supported OS	Win 7 / 10 / Android / Linux / Mac

OSD Function	
OSD Controls	5 buttons
OSD Languages	CN, EN, FR, IT, DE ES, KR, RU, PT

Mechanical	
Product Dimension	385.3 x 317.8 x 47 mm
Packing Dimension	493 x 439 x 155 mm(1 PCS) 532 x 460 x 322 mm(4 PCS)
Weight(approx.)	4.8kg / 6.2kg
Wall Mount Method	VESA, MIS-D, 100 x100 mm, Y, 4, 90

Power	
Power Supply	DC in: DC 12V, connector: 5.5*2.5
Typical Power	≤ 14W (typ.)
Standby Power	≤ 0.5 W (typ.)

Environmental	
Operating T&H	0 °C ~ 50 °C, 90% RH
Storage T&H	-20 °C ~ 60 °C, 90% RH

Accessories	
Active Stylus Pen	Included
Desktop base	P/N: DS100
Adapter	AC-DC, AC 100~240V 50/60hz DC 12V 3A, 5.5*2.5*10mm
Internal Speakers	Support 8Ω 5W

Other	
Ready for Use	7/24
Warranty	1 Year
Regulations	CCC, CE, FCC, CB, RoHS

※ Drawings

