


**MODEL: BF-P660**

**400V | 1500rpm | 50Hz**



<b>ESP</b> Standby Power	<b>660 kVA</b>	<b>PRP</b> Prime Power	<b>600 kVA</b>
<b>ENGINE</b>	<b>Perkins</b>	<b>ALTERNATOR</b>	<b>STAMFORD</b>
	<b>2806C-E18TAG1A</b>		<b>HCI544E1</b>

## GENERAL FEATURES

Engine: Perkins 2806C-E18TAG1A

Alternator: single bearing, IP23, insulation class H

50°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: BF-P660**

**400V | 1500rpm | 50Hz**

**GENERATOR RATINGS**

Voltage	Hz	Phase	PF ( COSΦ )	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	866	528kW/660kVA	480kW/600kVA
415/240	50	3	0.8	918	528kW/660kVA	480kW/600kVA
400/230	50	3	0.8	953	528kW/660kVA	480kW/600kVA
380/220	50	3	0.8	1003	528kW/660kVA	480kW/600kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 ( eqv ISO 8528 ) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

**SALES PROMISES**

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

**MODEL: BF-P660****400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Perkins 2806C-E18TAG1A
Air intake system	Turbocharged, air to air charge cooling
Fuel system	MEUI
Cylinder arrangement	6 in line
Displacement	18.13L
Bore and stroke	145×183 mm
Compression ratio	14.5:1
Rated speed	1500rpm
Max. Standby power at rated speed	583.5KW
Governor type	Electronic

**Exhaust System**

Exhaust gas flow	115 m <sup>3</sup> /min
Exhaust temperature	565°C
Max back pressure	6.9kPa

**Air Intake System**

Max intake restriction	6.35kPa
Combustion air flow	41 m <sup>3</sup> /min
Air flow required for radiator	702 m <sup>3</sup> /min



**MODEL: BF-P660**

**400V | 1500rpm | 50Hz**

**Fuel System**

Fuel consumption @ 100% (Prime Power) Load	216 g/kWh	131 L/h
Fuel consumption @ 75% (Prime Power) Load	214 g/kWh	97 L/h
Fuel consumption @ 50% (Prime Power) Load	212 g/kWh	65 L/h

**Oil System**

Total oil capacity	62L
Oil consumption ratio based on fuel consumption data	0.1%(As a percentage of fuel consumption)
Oil sump capacity	45~53L

**Cooling System**

Coolant capacity	61L
Max water temperature	103°C



**MODEL: BF-P660****400V | 1500rpm | 50Hz****ALTERNATOR SPECIFICATION**

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

**Alternator Data**

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	< 50
THF	< 2%
Alternator Capacity	610kVA
Alternator Efficiency	94.9%

**MODEL: BF-P660****400V | 1500rpm | 50Hz****GENERATING SET DATA**

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +20\%$
Transient voltage deviation (sudden power increase)	$\leq -15\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 4S$
Voltage recovery time (sudden power increase)	$\leq 4S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 0.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +10\%$
Transient frequency deviation (sudden power increase)	$\leq -7\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 3S$
Frequency recovery time (sudden power increase)	$\leq 3S$

**STANDARD FEATURES**

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB

**MODEL: BF-P660**

**400V | 1500rpm | 50Hz**

**OPTIONS**

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		


**DIMENSIONS & WEIGHT**



**Standard Configuration (open type)**

Overall Dimensions: 3600×1400×2100 mm

Weight: 4500 kg



**Soundproof Type**

Overall Dimensions: 5030×1660×2550 mm

Weight: 6500 kg

*Specifications are subject to change without notice.*

**BAIFA POWER (WUXI) LTD.**

**WEBSITE: WWW.BAIFAPOWER.COM**

**EMAIL: MARKETING@BAIFAPOWER.COM**

**TEL: +86-510-85342633**

Comprehensive Solutions For  
**POWER GENERATION**

