

MODEL: BF-DW350-60

440V | 1800rpm | 60Hz



ESP Standby Power	370kVA	PRP Prime Power	335kVA
ENGINE	Doosan P126TI-II	ALTERNATOR	STAMFORD S4L1D-D41

GENERAL FEATURES

Engine: Doosan P126TI-II

Alternator: single bearing, IP23, insulation class H

40°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: BF-DW350-60****440V | 1800rpm | 60Hz**

GENERATOR RATINGS

Voltage	Hz	Phase	PF (COSΦ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
480/277	60	3	0.8	445	296kW/370kVA	268kW/335kVA
460/266	60	3	0.8	464	296kW/370kVA	268kW/335kVA
440/254	60	3	0.8	486	296kW/370kVA	268kW/335kVA
416/240	60	3	0.8	514	296kW/370kVA	268kW/335kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

MODEL: BF-DW350-60

440V | 1800rpm | 60Hz

ENGINE SPECIFICATION

Manufacturer / Model	Doosan P126TI-II
Air intake system	Turbo, Air/Air cooling
Fuel system	P type fuel pump
Cylinder arrangement	6 in line
Displacement	11.051L
Bore and stroke	123×155 mm
Compression ratio	17
Rated speed	1800rpm
Max. Standby power at rated speed	342kW
Governor type	Electronic

Exhaust System

Exhaust gas flow	64.2 m ³ /min
Exhaust temperature	580°C
Max back pressure	5.8kPa

Air Intake System

Max intake restriction	6.1kPa
Combustion air flow	28.2 m ³ /min
Air flow required for radiator	722 m ³ /min

**MODEL: BF-DW350-60****440V | 1800rpm | 60Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load	73.8 L/h
--	----------

Fuel consumption @ 75% (Prime Power) Load	56 L/h
---	--------

Fuel consumption @ 50% (Prime Power) Load	37 L/h
---	--------

Oil System

Total oil capacity	25L
--------------------	-----

Oil sump capacity	20-23L
-------------------	--------

Cooling System

Coolant capacity	60L
------------------	-----

Max water temperature	103°C
-----------------------	-------

**MODEL: BF-DW350-60****440V | 1800rpm | 60Hz**

ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	370kVA
Alternator Efficiency	92.9%

MODEL: BF-DW350-60

440V | 1800rpm | 60Hz

GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB

MODEL: BF-DW350-60

440V | 1800rpm | 60Hz

OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		


DIMENSIONS & WEIGHT



Standard Configuration (open type)

Overall Dimensions: 2960×1030×1650 mm

Weight: 2315kg



Soundproof Type

Overall Dimensions: 3980×1560×2150 mm

Weight: 3750kg

Specifications are subject to change without notice.

BAIFA POWER (WUXI) LTD.

WEBSITE: WWW.BAIFAPOWER.COM

EMAIL: MARKETING@BAIFAPOWER.COM

TEL: +86-510-85342633

Comprehensive Solutions For
POWER GENERATION