


FPC/FPC DIMENSION  
THICKNESS 0.3±0.05mm



DETAIL A  
CLOSE TYPE

- NOTES:
1. MATERIALS:
    - Housing : PBT (UL94V-0)
    - Contacts : Phosphor Bronze
    - Plating : Tin over Nickel Plated
  2. SPECIFICATIONS:
    - Voltage Rating : 200V AC Max.
    - Current Rating : 1A Max.
    - Contact Resistance : 20 mΩ Max.
    - Insulation Resistance : 500 MΩ Min.
    - Withstanding Voltage : 500V AC RMS
    - Temperature Range : -40°C TO +85°C

NOTES

1. MATERIALS:  
HOUSING-PBT UL 94V-0,  
TERMINAL-PHOSPHOR BRONZE.


2. ORDER INFORMATION:  
AFD3-XX X X A X

CKT SIZE  
03 TO 32.


0: TOP ENTRY  
1: SIDE ENTRY

PLATING:  
0:Sn/Pb 90/10 120u"  
OVER 50u" NICKEL.  
G:LEAD-FREE

CKT	A	B
3	9.55	5.20
4	10.80	6.45
5	12.05	7.70
6	13.30	8.95
7	14.55	10.20
8	15.80	11.45
9	17.05	12.70
10	18.30	13.95
11	19.55	15.20
12	20.80	16.45
13	22.05	17.70
14	23.30	18.95
15	24.55	20.20
16	25.80	21.45
17	27.05	22.70
18	28.30	23.95
19	29.55	25.20
20	30.80	26.45
21	32.05	27.70
22	33.30	28.95
23	34.55	30.20
24	35.80	31.45
25	37.05	32.70
26	38.30	33.95
27	39.55	35.20
28	40.80	36.45
29	42.05	37.70
30	43.30	38.95
31	44.55	40.20
32	45.80	41.45



RECOMMEND PC BOARD  
HOLE DIMENSION  
正脚位



RECOMMEND PC BOARD  
HOLE DIMENSION  
反脚位

# 深圳扬讯电子有限公司

TOLERANCE: XX ±0.30 XXX ±0.20 XXXX ±0.05 X' ±1° XX' ±0.05° UNT: mm [inch] SCALE:1:1 SIZE: A4	DRAWN BY : 胡 捷	DATE : FPC 1P 1.25 PITCH NW-ZIP FOR 180° DIP	PART NAME:
CHECKED BY : 李国栋	DATE : AFD3-S**FCA-PD	DRAW NO.:	FPC 1.25 NP 180DIP
APPROVED BY :	DATE :	REMARK	
		MOULD NO.	