



规格说明: Specifications:

电气特性: Electrical:

- 额定电流: Current Rating
1.5A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触阻抗: Contact Resistance
30 milliohms MAX
- 耐电压: Dielectric Withstanding Voltage:
500 V AC At Sea Level
- 绝缘阻抗: Insulation Resistance:
1000 MEGA ohms MIN

原材料: Raw material:

- 塑胶: Plastic cement:
Hing Temperature Thermoplastics,
UL 94V-0 PBT/LCP White/Black
- 端子: Contact: Copper Alloy C2680
- 外壳: Shell: SPCC

电镀: Electroplate:

- 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
- 外壳: Shell:
Nickel Plating

深圳扬讯电子有限公司

品名 (ITEM NO)	USB A/M 90° 沉板式SMT (4.50) 弯脚	图号 (DWG NO)	1D	单位 (UNIT):	MM
料号 (PART NO)	UAR-AMM9-018-04	版本 (REV)	A/0	比例 (SCALE)	1:1
型号 (MODEL NO)	A031	日期 (DATE)	2012.02.04	设计 (DESIGN)	陈钦虎
		审核 (CHECKED)		公差	未注公差
		核准 (APPROVED)		TOLERANCE UNSPECIFIED	X X ±0.30
				X XX ±0.20	X XXX ±0.10
				X° ±5°	X X° ±2°