



- 特性: Specifications:**
- 电性能: Electrical:
    - 接触电阻: Contact Resistance: 30 milliohms MAX
    - 耐压: Dielectric Withstanding Voltage: 500 V AC AT Sea Level
    - 绝缘电阻: Insulation Resistance: 1000 MEGA ohms MIN
  - 机械: Mechanical:
    - 结合力: Mating Force: 4.0 KG MAX 最大4kg
    - 拔出力: Mating Force: 0.7 KG MIN. 最少0.7kg
  - 材料: Material:
    - 塑胶: Housing: 耐高温 Thermoplastics UL 94V-0 阻燃等级
    - 端子: Contact: Copper Alloy 铜合金
    - 外壳: Shell: Copper Alloy 铜合金
    - 电镀: Finish: Tin/ On Solder Tails
    - 端子: Contact: Plated Gold in Mating Area;
    - 接触点: Shell: Nickel Plating 镀镍

**深圳扬讯电子有限公司**

TOLERANCE: XX ±0.25 XXX ±0.20 XXXX ±0.10 X* ±1°		DRAWN BY: 周然东 DATE: 2008-8-13		PART NAME: USB AF 180° DIP	
UNITS: mm [inch] SCALE: 1:1 SIZE: A4		CHECKED BY: 周然东 DATE: 2008-8-13		DRAW NO.: YX-08-182	
APPROVED BY:		DATE:		PART NO.: 56604A0523332	
REMARK:		REMARK:		MOLD NO.:	